



CONCRETE & MASONRY
SPECIALTY COATINGS

TM

We Help You Seal Better®

Seal Pro PRO 1315 Data Sheet

Clear Cure-n-Seal High Gloss Spray
Exterior / Interior

Seal Pro PRO 1315 is an economical solvent base acrylic cure and seal formulated with easy application in mind. It will provide initial protection against the adhesion of mortar droppings, paint and stains. PRO 1315 is designed for curing freshly placed concrete by promoting proper hydration so the surface will achieve maximum hardness. Use PRO 1315 as a sealer on all concrete. **When a heavy duty, long lasting sealer is desired, use Seal Pro MS300 or Seal Pro 600. For absolute best results use MS300 for sub seal and Seal Pro 600 for top coat.**

SURFACE PREPARATION: Surface must be sound and properly finished. As a cure surface is ready for application when damp but not wet and can no longer be marred by walking workman. To seal, surface must be free of all contaminants and fully cured.

APPLICATION: PRO 1315 must be applied as packaged. Do not dilute or alter the product in any way. Do not thin. Spraying is the preferred method of application or can be rolled. Apply until surface has an even degree of sheen.

COVERAGE RATE: Weather conditions, porosity, texture of the surface and film build will determine the amount of product necessary for effective treatment. Total product required is 200 sqft. per gallon for curing and 200-400 sqft per gallon for sealing non-fresh concrete.

LIMITATIONS: Do not mix or apply under or over any other Seal Pro products. Do not use on concrete specified for acid stain. Do not let puddle during application.

PRECAUTIONS: Use with adequate ventilation to avoid buildup of fumes. Use approved OSHA breathing apparatus. Contains solvents. Do not spray near open flame. Do not store in direct sunlight or where temperatures exceed 140° F. Do not allow product to freeze. Avoid breathing spray mist and contact with skin.

ASTM C 309 requires 18% solids by mass and a loss in weight of no more than 0.55 kg/m² over a 72 hour period exposed to conditions of 100° F and 32% RH.

Seal Better!
Products and Services to Solve Problems

- Meets Type I Class B
- Meets ASTM C 309 & 1315
- Dust Proofs
- Excellent Early Water Retention
- Excellent Early Water Resistance
- High Gloss 27% Solids

Specifications:	
Form:	Water White to Clear Liquid
Solid Content:	≥27%
Specific Gravity:	1.06
Weight Per Gallon:	7.58 lbs
Flash Point (ASTM 3243):	79-F
VOC Content (ASTM D 3960-87):	≤682 Gr/Ltr
Shelf Life:	Indefinite
Pencil Hardness (ASTMD 3363):	B
Tukon Hardness (ASTMD 1474):	47A
Adhesion (ASTM D 3359):	Excellent
Chemical Resistance (ASTM D 1308-87) 12 Chemicals:	Good
Water Retention (ASTM C 1315)	Pass
Gloss (Gardner 60 Meter):	High
Exterior Durability:	Good
Dry Time:	78 F, 40% RH 92 Min. 40 F, 80% RH 205Min.
Vehicle:	Solvent

Manufactured By:
Seal Pro USA
551 Business Park Dr.
Medford, OR 97504
Phone 541.773.1914
www.sealprousa.com

MATERIAL SAFETY DATA SHEET

SEAL PRO PRO 1315

SECTION ONE: PRODUCTION IDENTIFICATION

TRADE NAME: SEAL PRO PRO 1315

Date of preparation: Revised 02.20.2013

Emergency phone: CHEMTREC 800.424.9300

HMIS Ratings: H-2 F-3 R-0

SEAL PRO USA 551 BUSINESS PARK DR. MEDFORD OR 97504

Phone 888.773.1914

SECTION TWO: HAZARDOUS INGREDIENTS

Components	PEL ppm	TLV ppm	Percent (%)
Aromatic 100*	100 ppm	100 ppm	-
Ethyl Acrylate*	5 ppm	5 ppm	.40 Max
Residual Monomers	NE*	NE*	.30 Max
Trade Secret Blend	-	-	-

*Subject to the reporting requirements of section 313 of the Emergency Planning and Community and Right To Know Act of 1986 and 40 CFR 372.

DOT SHIPPING INFORMATION

Proper shipping name: Resin Solution

Hazard classification: 3

UN number: 1866

Packing group: II

SECTION THREE: PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling point: 312 F

Vapor density Air = 1: >1

Solubility in water: Not soluble

Appearance and odor: Slightly amber liquid and solvent odor

Melting point: NE*

Specific gravity: .775

Vapor pressure: 4.18

Reactivity in water: Not reactive

*NE: Not established

SECTION FOUR: FIRE AND EXPLOSION DATA

Flash point: 79°F Method used: TCC
Flammable limits in air % by volume: LEL Lower: 1.0 | UEL Upper: 6.1
Auto ignition temperature: NE*
Extinguisher media: FOAM, CO2, DRY CHEMICAL, WATER SPRAY

Special Fire Fighting Procedures: Solid hoses streams tend to scatter liquid and spread fire. Water spray cools the burning surface and helps exclude air. Fire fighters should wear self-contained breathing apparatus operated in positive pressure mode.

Unusual fire and explosion hazards: Vapors are heavier than air and may travel along the ground to ignition sources (*heat, sparks, flame, etc.*) distant from the material handling point.
Never use welding or cutting torch on or near container even empty, because product or residue may ignite explosively.

SECTION FIVE: PHYSICAL HAZARDS (REACTIVITY DATA)

Stability: Stable
Incompatibility: Strong oxidizing agents.
Hazardous decomposition products: Carbon monoxide, carbon dioxide, various hydrocarbons.
Hazardous polymerization: Will not occur.
Conditions to avoid: Heat, sparks, open flame, static discharge.

SECTION SIX: HEALTH HAZARDS

Acute: Severe eye irritation, headache, moderate skin irritation.

Chronic: Ethyl Acrylate is listed by the National Toxicology Program and the International agency for Cancer as a potential cancer causing agent. A study found Ethyl Acrylate to be an animal carcinogen in a forced ingestion study on mice and rats. In an Inhalation study, rodents exposed to ethyl Acrylate vapors at 25 and 75 ppm for 27 months showed nonmalignant changes in nasal passage membranes.

Signs and symptoms of exposure: Painful eye irritation, redness of eyes, headache, nausea, vomiting, and dizziness. Possible skin rash. Symptoms will vary depending on the individual.

Medical conditions generally aggravated by exposure: Asthma and other respiratory ailments.
Any substance can be allergenic to an allergy pre-disposed individual.

Chemical listed as carcinogen or potential carcinogen:

NT: Yes
IARC: Yes
OSHA: Yes

Emergency and first aid procedures: Inhalation - remove to fresh air, call a physician.

Eyes - flush with copious amounts of water and seek medical attention. Skin - wash exposed area with soap and water. Ingestion - do not induce vomiting - aspiration of the material into lungs can cause chemical pneumonitis which can be fatal. Get immediate medical attention!

Routes of entry:

Inhalation - headache, nausea, vomiting, dizziness, fatigue, unconsciousness, asphyxiation.

Eyes - severe painful irritation, redness and blurred vision.

Skin - moderate irritation, defatting, dermatitis.

Ingestion - gastrointestinal irritation, nausea, vomiting, diarrhea. Choking may occur with vomit.

SECTION SEVEN: SPILL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Handling and storage precautions: Keep away from heat, sparks, and open flames. Use with adequate ventilation. Avoid contact with skin.

Containers may be hazardous when emptied. Since emptied containers retain residues (vapor, liquid, solid) all hazard precautions given in this MSDS must be observed.

If material is released or spilled: Small - absorb and transfer to appropriate waste container.

Large - eliminate all ignition sources, exclude workers not wearing protective gear, dike area, pump to grounded salvage tank. Absorb remainder and shovel into an appropriate waste container.

Waste disposal methods: Consult federal, state, and local regulations. Incinerate in accordance with local, state, and federal regulations.

SECTION EIGHT: SPECIAL PROTECTION INFORMATION AND CONTROL MEASURES

Respiratory protection: If TLV of product is exceeded, NIOSH / OSHA jointly approved air supplied respirator is advised. Normal conditions require the use of NIOSH / OSHA approved respirator fitted with solvent vapor approved cartridges.

Ventilation: Local exhaust, mechanical to maintain exposure below TLV.

Protective gloves: Solvent resistant gloves such as Buna-N.

Eye protection: Chemical splash goggles in compliance with OSHA.

Other protective clothing or equipment: Eye bath, safety shower, impervious clothing to prevent skin contact.

Work / Hygienic practices: Wash thoroughly after exposure, remove contaminated clothing and launder before reuse.

This data is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.